



# DRIVESHAFT ANDERSON, INC.

## NTN UCP211 P211 pillow block bearing



Bearing No. UCP211

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | NTN  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 3.5  |
| EAN                       | 4547359225365  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 16 Millimeter  |
| Relubricatable            | No   |
| Insert Part Number        | UC211  |
| Seals                     | Single Lip Land Riding   |
| Housing Configuration     | 1 Piece Solid  |
| Inch - Metric             | Metric   |
| Other Features            | Single Row   Light Duty   Wide Inner Race   Has Flinger  |
| Long Description          | 2 Bolt Pillow Block; 55MM Bore; 63.5MM Base to Center Height; Set Screw Mount; Ball Bearing; No Relubricatable; Cast Iron; Single Lip Land Riding; Non-expansion |

UCP211 Bearing 2D drawings and 3D CAD models



## DRIVESHAFT ANDERSON, INC.

|                               |   |
|-------------------------------|---|
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.40   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a> |
| Manufacturer Item Number      | UCP211  |
| Weight / LBS                  | 7.716   |
| D                             | 2.189 Inch   55.6 Millimeter                                      |
| Actual Bolt Center to Center  | 6.7 Inch   170 Millimeter   |
| Nominal Bolt Center to Center | 6.8 Inch   171.5 Millimeter                                       |
| Bolt Spacing Maximum          | 0 Inch   0 Millimeter   |
| B                             | 2.5 Inch   63.5 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0 Millimeter   |
| d                             | 2.165 Inch   55 Millimeter  |